

## Industrial Heater

## Control Technology

Modular heating system

### MHS Controller CANopen

The controller is a fieldbus device for the control of up to 7 power modules from the modular heating System from Kendrion, which are directly connected via the module bus. In addition to system monitoring, the controller can also control or regulate the individual output channels of all power modules. Actual temperature values can be delivered directly via CAN fieldbus or provided by a higher-level controller e.g. a PLC.

Extensive diagnostic options as well as integrated inputs and outputs enable fast commissioning.



#### Features

- CANopen Fieldbus interface
- Independent control of up to 7 induction generators
- System monitoring, temperature control
- Integrated I/Os and CAN system bus



Technical Data	MHS Controller CANopen
Fieldbus interface	CANopen (Addressing and speed via dip switches)
Interfaces	1 x Ethernet 10/100Mbit (on request)
Module bus / module supply	CAN / 24 VDC, 2,5 A (max. 7 Module)
System bus	CAN, galvanically isolated (e.g. for the acquisition of temperature data)
Status indication	Heating system, CANopen, DC power supply
Functions	Temperature control, system monitoring, fieldbus communication, bus coupler for up to 7 MHS power modules, power control, Software update via SD card
Integrated I/O	on request: 8 x DI: input delay: 3 ms / 8 x DO 24V, 0,5 A, Short circuit protection
Housing	IP 20, module made of steel with stainless steel cover for use in a closed, metallic control cabinet
Assembly	Prepared for left-side mounting on the power module
Dimension (H x B x T)	451 mm x 44 mm x 286 mm
Supply voltage	24 V DC (-10% +25%); current consumption internal 0,5 A
Operating temperature	In vertical installation position: 0°C ... 35°C
Certifications	CE, cULus (in preparation)

NH3322

We reserve the rights of modification, omission, error with respect to the products. Illustrations similar. All rights reserved by the individual copyright holders. EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Safety over EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Microsoft®, Windows® and the Windows® Logo are registered trademarks of Microsoft Corporation in the USA and other countries. At [www.plcopen.org](http://www.plcopen.org) you will find more information about PLCopen Organisation. CODESYS is a product of 3S-Smart Software Solutions GmbH. CiA® and CANopen® are registered community trademarks of CAN in Automation e.V., PROFINET and the PROFINET logo are registered trademarks of the PROFIBUS user organization (PNO).